

DS-D42AM2 LED Multi-functional Card

LED multi-functional card is an (optional) accessory for 3D scene display and remote control in LED display system. This product is equipped with remote control and infrared signal receiver by default, which can realize multi-functions including multi-scene switch, signal source switch, brightness control, system information check, intelligent dehumidification, anti-blue light, and image enhancement, etc.



Key Feature

- Support network interface cascading between or behind the receiving card;
- Support infrared signal input.





Specification

Model		DS-D42AM2	
Control Card Parameter	Sending Card Dimension (W× H × D)	200 × 42 × 126.7 mm (7.9 × 1.7 × 5.0 inch)	
	Sending Card Weight	0.70 kg (1.5 lb)	
Electrical Parameter	Power Supply	12 VDC, 1A	
	Peak Power	8 W	
	Average Power	3 W	
General	Working Temperature	-10 to + 40 °C (+14 to +104 °F)	
	Working Humidity	10 to 90 %	
	Storage Temperature	-20 to + 60 °C (-4 to +140 °F)	
	Storage Humidity	10 to 90 %	
	Package Dimension (W × H × D)	317 × 82 × 242 mm (12.5 × 3.2 × 9.5 inch)	
	Gross Weight	0.75 kg (1.7 lb)	
	Packing List	multi-functional card × 1, infrared remote control × 1, power adapter × 1, outer package × 1	


Available Model

DS-D42AM2




Physical Interface

Front panel is as shown below.



Name	Description	Name	Description
12V GND	Sensor interface	RS232	Serial port, used for remote communication
3.3V GND (SCL SDA)	Sensor interface	POWER	Indicator light of power supply
AI/DI GND	Sensor interface	ACTIVE	Indicator light of proper function
RS485	Serial port, used for remote communication		

Back panel is as shown below.



Interface	Description	Interface	Description
IR IN	Infrared remote control interface for connecting infrared extension cable	DATA	Multi-functional card interface, cascaded with receiving card
IR OUT	Infraed output	WLAN	Network interface
3D OUT	Reserved	DC IN 12V	Power supply



Typical Application



LED Sending Card

Distributed by

.

HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA

T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 [10] 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hlkvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com