

LYONN UPS



MODELO	DESIRE 500 LED	DESIRE 500 LCD	CTB 800 LED	CTB 800 LCD	CTB 1200 LED	CTB 1200 LCD	CTB 1500 LED	CTB 1500 LCD	CTB 2000 LED	CTB 2000 LCD	CTB 2500 LCD	CTB 3000 LCD
CAPACIDAD	500VA	500VA	800VA	800VA	1200VA	1200VA	1500VA	1500VA	2000VA	2000VA	2500VA	3000VA
ENTRADA												
Voltaje	220/230/240 vac											
Rango de volataje	162-290 VAC											
SALIDA												
AC Regulación de	+/-10%											
Tiempo de transferencia	Tipico 2-6 ms, máximo 10 ms											
Forma de onda	Onda Sinusoidal Simulada											
BATERIAS												
Tipo de baterías	12V/4,5AH	12V/4,5AH	12V/7AH	12V/7AH	12V/7AH	12V/7AH	12V/7AH	12V/9AH	12V/7AH	12V/9AH	12V/9AH	12V/9AH
Cantidad	1	1	1	1	2	2	2	2	2	2	2	4
Tipo de recarga	4-6 horas para recuperar al 90% de la capacidad de las baterías internas a una corriente de carga de 2A											
FISICA												
Dimension, Largo X	279 x 101 x 142	300 x 101 x 142	279 x 101 x142	300 x 101 x 142	320 x 130 x 182						380 x 158 x 198	495 x 150 x 250
Peso (kgs)	3,55	3,7	4,2	4,4	8,2			10,4		10,6		24,8
AMBIENTE												
Humedad	0-90 % RH @ 0- 40°C (sin condensación)											
Nivel de emisión de ruido	Menos de 40 dB											
GESTION												
USB	Soporta Windows® 2000/2003/XP/Vista/2008/7/8, Linux, Unix											